

Citadel Series

Versatile 12 amp protection for computers, servers, test equipment, security, POS, controllers and audio.

- ⚡ Surge Protection
- ⚡ Power Conditioning & Filter
- ⚡ Stable Ground Reference
- ⚡ Harmonic Attenuation
- ⚡ PLE Suppression

120 V · NORTH AMERICA

RM1440A

1440 VA · 12 A · 110-120 VAC · 50-60 Hz



Full-width protection behind North American racks, benches and equipment closets.

Outlets	6 NEMA 5-15R + 2 rear IEC 320 C13; two C13-to-NEMA adapters included
Circuit protection	Thermal breaker, push-to-reset
Display	Color LCD, real-time metrics

Listed to UL 62368-1

3-year replacement

220-230 V · INTERNATIONAL

RM2880A

2880 VA · 12 A · 220-230 VAC · 50-60 Hz



The same patented circuit for 220-230 V installations worldwide, server rooms to broadcast racks.

Outlets	8 filtered IEC 320 C13
Circuit protection	Thermal breaker, push-to-reset
Display	Color LCD, real-time metrics

Listed to UL 62368-1

3-year replacement



One chassis, deployed your way

The Citadel installs in a standard equipment rack with its mounting ears, stands upright on its vertical stand, or sits flat on a shelf, floor or wall position. Its front-panel color LCD reports six power metrics in real time.



RM1440A rear panel



RM2880A rear panel

Performance, Shared Across the Series

Surge suppression design	Series mode protection; energy suppression is not joule-limited
Surge protection life	Surge events do not damage the patented circuit; protection is always active
Circuit protection	Thermal breaker, push-to-reset
Real-time display	Surge count · voltage · current · frequency · wattage · power factor
Regulatory compliance	UL 62368-1
Warranty	3-year full replacement

EMI/RFI Attenuation (Normal Mode)

Frequency	Reactance	RM1440A	RM2880A
60 Hz	1.51 Ω	0.30 dB	0.14 dB
180 Hz (3rd harmonic)	4.52 Ω	0.98 dB	0.36 dB
300 Hz (5th harmonic)	7.54 Ω	2.09 dB	0.77 dB
420 Hz (7th harmonic)	10.55 Ω	3.35 dB	1.32 dB
1 kHz	25.12 Ω	8.67 dB	4.62 dB
10 kHz	251 Ω	28.0 dB	22.7 dB
150 kHz	3.77 kΩ	51.5 dB	46.2 dB
1 MHz	25.1 kΩ	68.0 dB	62.7 dB

Low attenuation at 60 Hz is by design: power passes freely while noise is progressively blocked.

⚡ PLE suppression, standard in every Bantam circuit

Suppresses power-line emissions (PLE): unwanted high-frequency signals that ride along power wiring, blocking them bi-directionally so they neither leak off your equipment nor couple onto it from the line.

Intellectual Property · U.S. Patents

8,223,468

Power Conditioning Circuit Utilizing High Overstated Rating Inductors

11,775,645 · 12,019,751 · 12,271,477

Suppression of Signal Transmission over a Conductor

One patented circuit. Every product.

Surge protection, power conditioning, a stable ground reference, harmonic attenuation, power factor correction and PLE suppression, engineered into every Bantam product from portable point-of-use units to OEM components.

Computers & Servers

Gaming, Kiosk & ATM

Professional Audio & Video

Hospitality & Point of Sale

Security & Surveillance

Industrial Controllers & Instrumentation

POINT OF USE

Vanguard Series

PP3002B • PP3004A • PP18004A

Portable and compact, the Vanguard packs patented power conditioning and surge protection into a small, affordable package for home, office and pro-AV use.

Input / output	110-120 VAC single phase • 15 A
Outlets	Filtered NEMA 5-15R (2 or 4)
Circuit protection	15 A thermal breaker, push-to-reset

Listed to UL 1449 by MET Labs

RACK, FLOOR OR WALL MOUNT

Citadel Series

RM1440A (120 V) • RM2880A (220-230 V)

Versatile 12 A protection for computers, servers, test equipment, security, POS, controllers and audio, with a color LCD showing surge count, voltage, current, frequency, wattage and power factor in real time.

RM1440A	1440 VA • six NEMA 5-15R + two IEC 320 C13
RM2880A	2880 VA • eight IEC 320 C13
Circuit protection	Thermal breaker, push-to-reset

Listed to UL 62368-1

OEM COMPONENT

Tempest SA3600A

85-250 VAC input • 3600 W • 10-15 A

The patented Bantam circuit as a UL component listed module, so OEMs can build superior surge protection and power conditioning into a wide variety of products.

Connections	3 each 0.25" QC spade connectors
Frequency	50 to 60 Hz • power factor 0.99
Circuit protection	None required

UL 62368-1 component listed • CE

UNINTERRUPTIBLE POWER

Nexus UPS Series

Nexus 360 • 800 • 1200 • 1500

Battery-backed continuity built on the same patented Bantam conditioning circuit, so protected equipment rides through outages on clean, conditioned power. Launching 2026.

Family	Four models spanning desktop to rack loads
--------	--

Launching 2026

Standard across the line: PLE suppression

Suppresses power-line emissions (PLE): unwanted high-frequency signals that ride along power wiring, blocking them bi-directionally so they neither leak off your equipment nor couple onto it from the line.

Every Bantam product embodies all four active U.S. patents

8,223,468 Power Conditioning Circuit Utilizing High Oersted Rating Inductors
11,775,645 • 12,019,751 • 12,271,477 Suppression of Signal Transmission over a Conductor